

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

PROOFMATE TX-S B-Komponente

UFI:

DEXN-0VH4-Q0KC-C8WE

1.2. Relevant identified uses of the substance or mixture and uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

TPH Bausysteme GmbH

Nordportbogen 8

22848 Norderstedt

Germany

Telephone: +49 40 52 90 66 78-0

Telefax: +49 40 52 90 66 78-78

E-mail: info@tph-bausysteme.com

Website: www.tph-bausysteme.com

E-mail (competent person): sdb-info@tph-bausysteme.com

1.4. Emergency telephone number

24h: International access phone number: +1-813-248-0585 /// United States, Canada, Puerto Rico, U.S. Virgin Islands: 1-800-255-3924 (Contract No. MIS7249185) /// Australia: 1-300-954-583 /// Brazil: 0-800-591-6042 /// China: 400-120-0751 /// India: 000-800-100-4086 /// Mexico: 800-099-0731

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2

TPH.
waterproofing systems

PROOFMATE TX-S B-Komponente

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05

Corrosion



GHS07

Exclamation mark

Signal word: Danger

Hazard statements for health hazards

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

Hazard statements for environmental hazards

H412	Harmful to aquatic life with long lasting effects.
------	--

Supplemental hazard information: —

Precautionary statements Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

Precautionary statements Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/....

Precautionary statements Disposal

P501	Dispose of contents/container to
------	---------------------------------------



2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 2855-13-2 EC No.: 220-666-8 REACH No.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Acute Tox. 4 (H302, H312), Aquatic Chronic 3 (H412), Eye Dam. 1 (H318), Skin Corr. 1B (H314), Skin Sens. 1A (H317)  Danger Specific concentration limit (SCL) Skin Sens. 1A; H317: C ≥ 0.001%	35 - < 60 weight-%
CAS No.: 100-51-6 EC No.: 202-859-9 REACH No.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4 (H332, H302)  Warning	29 - < 50 weight-%

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)


Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 103-83-3 EC No.: 203-149-1 REACH No.: 01-2119529232-48-XXXX	benzylidimethylamine Acute Tox. 4 (H332, H312, H302), Aquatic Chronic 3 (H412), Flam. Liq. 3 (H226), Skin Corr. 1B (H314)  Danger	2 - < 5 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. Get immediate medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

Rinse mouth. Let water be drunk in little sips (dilution effect). Get medical advice/attention if you feel unwell. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation Allergic reactions Serious eye damage/eye irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Water (with cleaning agent)

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
CZ	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 8.88 ppm (40 mg/m ³) ② 17.76 ppm (80 mg/m ³)
PL	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 240 mg/m ³
LT	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 mg/m ³ ⑤ (tikėtinas įsisavinimas per odą)
HTP (FI)	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 10 ppm (45 mg/m ³)
BG	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 mg/m ³
LV	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 mg/m ³
TRGS 900 (DE)	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 ppm (22 mg/m ³) ② 10 ppm (44 mg/m ³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden)
CH	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 ppm (22 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
SI	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	① 5 ppm (22 mg/m ³) ② 10 ppm (44 mg/m ³) ⑤ (računati je treba z možnostjo prodiranja skozi kožo)
JP	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	③ 25 mg/m ³
RU	benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	③ 5 mg/m ³
BG	benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	① 5 mg/m ³
RO	benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	① 0.9 ppm (5 mg/m ³) ② 1.8 ppm (10 mg/m ³)
LV	benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	① 5 mg/m ³
RU	benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	③ 5 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn Breakthrough times and swelling properties of the material must be taken into consideration. EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well.

Respiratory protection:

Filtering device with filter or ventilator filtering device of type: A A

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: light yellow

Odour: not determined

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	10	20 °C	② 20g/l
Melting point	<i>not determined</i>		
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	> 200 °C		
Decomposition temperature	<i>not determined</i>		
Flash point	101 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	<i>not determined</i>		
Upper/lower flammability or explosive limits	<i>not determined</i>		
Vapour pressure	0.3 hPa	20 °C	
Vapour density	<i>not determined</i>		
Density	0.99 g/cm ³	23 °C	① EN ISO 2811-1
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	partially miscible		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	<i>not determined</i>		
Solvent content	47 %	20 °C	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Acids

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Substance name	Toxicological information
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 EC No.: 220-666-8	LD₅₀ oral: 1,030 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rabbit)
benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	LD₅₀ oral: 1,620 mg/kg (Rat) LD₅₀ dermal: 2,000 mg/kg (Rabbit)
benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	LD₅₀ oral: 579 mg/kg (Rat) LD₅₀ dermal: 1,477 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (vapour): 2.06 mg/l 4 h (rat)

Acute oral toxicity:

Harmful if swallowed.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes severe skin burns and eye damage.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

Substance name	Toxicological information
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 EC No.: 220-666-8	LC ₅₀ : 110 mg/l 4 d (Leuciscus idus (golden orfe)) EC ₅₀ : 23 mg/l 2 d (Daphnia magna (Big water flea))
benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	LC ₅₀ : 460 mg/l 4 d (Pimephales promelas (fathead minnow)) EC ₅₀ : 230 mg/l 2 d (Daphnia magna (Big water flea)) EC ₅₀ : 770 mg/l 3 d (Algae/water plant)
benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	LC ₅₀ : 37.8 mg/l 4 d (fish) ErC ₅₀ : 1.34 mg/l 3 d (Desmodemus subspicatus)

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Substance name	Results of PBT and vPvB assessment
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS No.: 2855-13-2 EC No.: 220-666-8	—
benzyl alcohol CAS No.: 100-51-6 EC No.: 202-859-9	—
benzyl dimethylamine CAS No.: 103-83-3 EC No.: 203-149-1	—

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2

TPH.
waterproofing systems

PROOFMATE TX-S B-Komponente

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 01 11 * Waste paint and varnish containing organic solvents or other dangerous substances





*: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name			
POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, benzyldimethylamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, benzyldimethylamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, benzyldimethylamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, benzyldimethylamine)
14.3. Transport hazard class(es)			
 8	 8	 8	 8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 80 Classification code: C7 Tunnel restriction code: (E)	Special provisions: 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: C7	Special provisions: 223 274 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-B	Special provisions: A3 Limited quantity (LQ): Y841 Excepted Quantities (EQ): E1

14.7. Maritime transport in bulk according to IMO instruments

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

[DE] National regulations

Water hazard class

WGK:

2 - deutlich wassergefährdend

Other regulations, restrictions and prohibition regulations

MAL-kode (Denmark): 00-5

MAL-kode (Denmark): 00-5 (Ready-for-use mixture)

ZH 1/129 "Merkblatt: Reizende Stoffe/Ätzende Stoffe (M 004)"

ZH 1/301 "Merkblatt: Polyester- und Epoxid-Harze (M 023)"

[DK] National regulations

Other regulations, restrictions and prohibition regulations

MAL-kode (Denmark): 00-5

MAL-kode (Denmark): 00-5 (Ready-for-use mixture)

15.2. Chemical Safety Assessment

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Skin corrosion/irritation (<i>Skin Corr. 1B</i>)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Dam. 1</i>)	H318: Causes serious eye damage.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 28 Jan 2022

Print date: 14 Feb 2022

Version: 2



PROOFMATE TX-S B-Komponente

Hazard statements

H318	Causes serious eye damage.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available