according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

PUR-O-STOP FS-TX

UFI:

RJCM-8HF1-TY8P-EMUN

1.2. Relevant identified uses of the substance or mixture and uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor): TPH Bausysteme GmbH

Nordportbogen 8 22848 Norderstedt Germany **Telephone:** +49 40 52 90 66 78-0

Telefax: +49 40 52 90 66 78-78

E-mail: info@tph-bausysteme.com

Website: www.tph-bausysteme.com

E-mail (competent person): sdb-info@tph-bausysteme.com

1.4. Emergency telephone number

24h: GIZ-Nord +49 551 / 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification pro cedure
Acute toxicity (oral) (Acute Tox. 4)	H302: Harmful if swallowed.	
Skin corrosion/irritation (Skin Corr. 1)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. ()	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:





GHS08 Health hazard

Signal word: Danger

Hazard components for labelling: 4,4'-methylenebis(cyclohexylamine)

TPH Bauysteme GmbH

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

hazard statements for health hazards

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure. ()

Supplemental hazard information

EUH208 Contains 4,4'-methylenebis(cyclohexylamine). May produce an allergic reaction.

Precautionary statements Prevention

recationary statements revention		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

Preca	utionary stat	ements Response	

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concen- tration
CAS No.: 1761-71-3 EC No.: 217-168-8	 4,4'-methylenebis(cyclohexylamine) Acute Tox. 4, Eye Dam. 1, STOT RE 2, Skin Corr. 1B, Skin Sens. 1B ♦ ♦ ♦ Danger H302-H314-H317-H373 	50 - 100 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/ attention if you feel unwell.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. Get immediate medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

Following ingestion:

Rinse mouth. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell. Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed Skin corrosion/irritation Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam Extinguishing powder Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire: Gases/vapours, toxic Nitrogen oxides (NOx) Carbon monoxide Carbon dioxide (CO2)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Storage class: 8A – Combustible corrosive substances

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
RU	4,4'-methylenebis(cyclohexy lamine) CAS No.: 1761-71-3 EC No.: 217-168-8	③ 2 mg/m ³
TRGS 900 (DE)	Hydrocarbons, TRGS 900	 0 mg/m³ Mass fraction (wt %): 0

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection DIN EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Filtering device with filter or ventilator filtering device of type: A

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Odour: Amines Colour: light yellow

Safety relevant basis data

parameter		at °C	Method	Remark
рН	not determined			
Melting point	< -15 °C			
Freezing point	not determined			
Initial boiling point and boiling range	> 300 °C			
Decomposition temperature	not determined			
Flash point	> 150 °C			
Evaporation rate	not determined			
Auto-ignition temperature	not determined			
Upper/lower flammability or explosive limits	not determined			
Vapour pressure	not determined			
Vapour density	not determined			
Density	0.92 g/cm ³	23 °C	EN ISO 2811-1	
Bulk density	not determined			
Water solubility	not determined			
Partition coefficient: n-octanol/ water	not determined			
Dynamic viscosity	21 mPa*s	23 °C	DIN EN ISO 2555	
Kinematic viscosity	not determined			

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Acid Oxidising agent, strong

10.6. Hazardous decomposition products

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1. Information on toxicological effects			
Substance name	Toxicological information		
4,4'-methylenebis(cyclohexylamine)	LD ₅₀ oral:		
CAS No.: 1761-71-3 EC No.: 217-168-8	380 mg/kg (Rat)		
	LD ₅₀ dermal:		
	2,110 mg/kg (Rat) OECD 402		
Acute oral toxicity:			
Harmful if swallowed.			
Acute dermal toxicity:			
Based on available data, the classification	on criteria are not met.		
Acute inhalation toxicity:			
Based on available data, the classification	on criteria are not met.		
Skin corrosion/irritation:			
Causes severe skin burns and eye dama	ige.		
Serious eye damage/irritation:			
Based on available data, the classification	on criteria are not met.		
Respiratory or skin sensitisation:			
	tains 4,4'-methylenebis(cyclohexylamine). May		
produce an allergic reaction.			
Germ cell mutagenicity:			
Based on available data, the classification	on criteria are not met.		
Carcinogenicity:			
Based on available data, the classification	on criteria are not met.		
Reproductive toxicity:			
Based on available data, the classification	on criteria are not met.		
STOT-single exposure:			
Based on available data, the classification	on criteria are not met.		
STOT-repeated exposure:			
May cause damage to organs through p	rolonged or repeated exposure.		
Aspiration hazard:			
Based on available data, the classification	on criteria are not met.		
Additional information:			
No data available			
SECTION 12: Ecological informa	tion		
12.1. Toxicity			
	Toxicological information		
Substance name	Toxicological information		

Substance name	Toxicological information
4,4'-methylenebis(cyclohexylamine) CAS No.: 1761-71-3 EC No.: 217-168-8	LC ₅₀ : >100 mg/l 4 d (fish, Leuciscus idus (golden orfe)) DIN 38412 / part 15 EC ₅₀ : 6.84 mg/l 2 d (Daphnia magna (Big water flea)) OECD 202
	 ErC₅₀: 141.2 mg/l 3 d (Algae/water plant, Desmodesmu s subspicatus) DIN 38412 / part 9 NOEC: 4 mg/l 21 d (Daphnia magna (Big water flea)) OECD 211

12.2. Persistence and degradability

Substance name	Biodegradation	Remark
4,4'-methylenebis(cyclohexylamine)	Yes, slowly	1
TPH Bauysteme GmbH	Page 6/9	en / DK / TW / SM / AD / UA /
		GeSi.de

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

Substance name		Biodegradation	Remark
CAS No.: 1761-71-3 EC No.: 217-168-8			
.2.3. Bioaccumulat	ive potential		
Substance name		Log K _{OW} Bio	oconcentration factor (BCF)
4,4'-methylenebis(cyclohe CAS No.: 1761-71-3 EC No.: 217-168-8	xylamine)	2.03	
12.4. Mobility in so i No data available	il		
12.5. Results of PB	Г and vPvB assessme		
Substance name		Results of PBT and vP	
4,4'-methylenebis(cyclohe CAS No.: 1761-71-3 EC No.: 217-168-8	xylamine)	The substance in the mi vPvB criteria according t	xture does not meet the PBT/ to REACH, annex XIII.
12.6. Other adverse No data available	e effects		
SECTION 13: Disp	osal consideration	IS	
13.1. Waste treatm	ent methods		
13.1.1. Product/Pacl			
	signations according to I	EWC/AVV	
Waste code product			
•	ttoms and reaction residues		
: Evidence for disposal mus	t be provided.		
Waste treatment op	tions		
Appropriate disposa		expert about waste di	sposal.
	sport information		
	-	Sea transport	Air transport
Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1. UN-No.			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper sh	ipping name		
POLYAMINES, LIQUID,	POLYAMINES, LIQUID,	POLYAMINES, LIQUIE), POLYAMINES, LIQUID,
CORROSIVE, N.O.S.	CORROSIVE, N.O.S.	CORROSIVE, N.O.S.	CORROSIVE, N.O.S.
(4,4'-methylenebis(c	(4,4'-methylenebis(c	(4,4'-methylenebis(
yclohexylamine))	yclohexylamine))	yclohexylamine))	yclohexylamine))
14.3. Transport haz	ard class(es)		
()	A CONTRACTOR		T. E.

8

8

8

8

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.4. Packing group)		
II	П	II	II
14.5. Environmenta	l hazards]
No	No	No	No
14.6. Special preca	utions for user		
Special provisions: 274	Special provisions: 274	Special provisions: 274	Special provisions: A3
Limited quantity (LQ): 1 L	Limited quantity (LQ): 1 L	Limited quantity (LQ): 1 L	Limited quantity (LQ): Y840
Excepted Quantiti es (EQ): E2	Excepted Quantitie s (EQ): E2	Excepted Quantitie s (EQ): E2	Excepted Quantiti es (EQ): E2
Hazard identificati on number (Kemle r No.): 80	Classification code: C7 Remark:	EmS-No.: F-A, S-B Remark:	Remark:
Classification code: C7			
tunnel restriction code: (E)			
Remark:			

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

[DE] National regulations

Water hazard class

WGK:

3 - stark wassergefährdend

Other regulations, restrictions and prohibition regulations ZH 1/129 "Merkblatt: Reizende Stoffe/Ätzende Stoffe (M 004)"

15.2. Chemical Safety Assessment

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 7 Jan 2021 Version: 2



PUR-O-STOP FS-TX

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification pro cedure
Acute toxicity (oral) (Acute Tox. 4)	H302: Harmful if swallowed.	
Skin corrosion/irritation (Skin Corr. 1)	H314: Causes severe skin burns and eye damage.	
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. ()	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements		
H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H373	May cause damage to organs through prolonged or repeated exposure. ()	

16.6. Training advice

No data available

16.7. Additional information

No data available